

Product data sheet

Specifications



Auxiliary contact block, TeSys Giga contactor, 1NO + 1NC, lateral face side mounting, push-in terminals L1/R1

LAG8N113P

Product availability: Stock - Normally stocked in distribution facility

Price*: 13.00 USD

Main

Range Compatibility	TeSys G LC1G
Range Of Product	TeSys G
Range	TeSys
Device Short Name	LAG8N
Product Or Component Type	Auxiliary contact block
Auxiliary Contacts Operation	Instantaneous
Pole Contact Composition	1 NO + 1 NC
Connections - Terminals	screw clamp terminals 0.00...0.00 in ² (0.75...2.5 mm ²)solid stranded without cable end screw clamp terminals 0.00...0.00 in ² (0.75...2.5 mm ²)flexible with cable end

Complementary

Mounting Location	Side
[Ui] Rated Insulation Voltage	500 V IEC 60947-5-1 500 V CSA 500 V UL
[Ue] Rated Operational Voltage	500 V AC 25...400 Hz
[Ith] Conventional Free Air Thermal Current	10 A (at 140 °F (60 °C))
Rms Rated Making Capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
Permissible Short-Time Rating	100 A 140 °F (60 °C) 1 s 120 A 140 °F (60 °C) 500 ms 140 A 140 °F (60 °C) 100 ms
Protection Type	GG fuse 10 A
Mechanical Durability	8 Mcycles
Minimum Switching Current	1 mA
Minimum Switching Voltage	17 V
Non-Overlap Time	1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact
Insulation Resistance	> 10 MOhm
Height	2.20 in (55.8 mm)
Width	0.61 in (15.4 mm)
Depth	3.34 in (84.8 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight	0.11 lb(US) (0.05 kg)
------------	-----------------------

Environment

Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB 14048.5
-----------	--

Product Certifications	CB Scheme CCC cULus CE UKCA EU-RO-MR by DNV-GL EAC
------------------------	--

Ip Degree Of Protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

Protective Treatment	TH
----------------------	----

Ambient Air Temperature For Operation	-13...140 °F (-25...60 °C)
---------------------------------------	----------------------------

Ambient Air Temperature For Storage	-76...176 °F (-60...80 °C)
-------------------------------------	----------------------------

Operating Altitude	9842.52 ft (3000 m)
--------------------	---------------------

Ordering and shipping details

Category	22328-TESYS GIGA ACCESSORIES
----------	------------------------------

Discount Schedule	112
-------------------	-----

Gtin	03606481047892
------	----------------

Returnability	Yes
---------------	-----

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	1.38 in (3.5 cm)
------------------	------------------

Package 1 Width	2.68 in (6.8 cm)
-----------------	------------------

Package 1 Length	3.74 in (9.5 cm)
------------------	------------------

Package 1 Weight	2.01 oz (57.0 g)
------------------	------------------

Unit Type Of Package 2	S02
------------------------	-----

Number Of Units In Package 2	64
------------------------------	----

Package 2 Height	5.91 in (15.0 cm)
------------------	-------------------

Package 2 Width	11.81 in (30.0 cm)
-----------------	--------------------

Package 2 Length	15.75 in (40.0 cm)
------------------	--------------------

Package 2 Weight	8.77 lb(US) (3.979 kg)
------------------	------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

✓ Pvc Free

✓ Halogen Free Plastic Parts Product

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
